


160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws,
0.6 x 3.5 x 100 mm
Kraftform Plus – Series 100 VDE



EAN:	4013288160089	Size:	181x26x26 mm
Part number:	05006440001	Weight:	35 g
Article number:	160 iS	Country of origin:	CZ
		Customs tariff number:	82054000

- Insulated blades for secure work at 1,000 volts
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Take it easy tool finder: colour coding according to profile and size
- Hexagonal anti-roll feature against rolling away
- Reduced shaft diameter

Reduced blade diameter with integrated protective insulation, low-lying screw and spring elements can be easily reached and operated. Kraftform Plus handle for comfortable ergonomic screwdriving, which avoids blisters and calluses. Hard handle zones for high working speeds, while soft handle zones guarantee a high torque transfer. Take it easy tool finder with colour coding by profile and size stamping - for quick and easy identification of the required tool . Anti-roll protection avoids bits from rolling away annoyingly at the workplace.



Web link

https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_160_is.html

Wera - 160 iS
05006440001 - 4013288160089

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de


**160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws,
0.6 x 3.5 x 100 mm
Kraftform Plus – Series 100 VDE**



VDE-insulated screwdriver with reduced blade diameter



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Impact strength test



Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces - resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

Prevents hand injuries




The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

Take it easy Tool Finder



Screwdrivers with Take it easy tool finder: colour coding according to profile and size stamp.

Web link
https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_160_is.html







Wera - 160 iS
05006440001 - 4013288160089

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws,
 0.6 x 3.5 x 100 mm
 Kraftform Plus – Series 100 VDE



Further versions in this product family:

	 mm	 mm	 mm	 mm	 inch	 inch
05006440001	0.6	3.5	100	81	9/64"	4"
05006441001	0.8	4.0	100	98	5/32"	4"
05006442001	1.0	5.5	125	98	7/32"	5"

Web link
https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_160_is.html

Wera - 160 iS
 05006440001 - 4013288160089

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de