

165 iS PZ VDE Insulated screwdriver with reduced blade diameter for Pozidriv screws, PZ 1 x 80 mm
Kraftform Plus – Series 100 VDE



EAN:	4013288160188	Size:	178x33x33 mm
Part number:	05006460001	Weight:	57 g
Article number:	165 iS	Country of origin:	CZ
		Customs tariff number:	82054000

- Insulated blades for secure work at 1,000 volts
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Take it easy tool finder: colour coding according to profile and size
- Hexagonal anti-roll feature against rolling away
- Reduced shaft diameter

Wera VDE screwdriver with multi-component Kraftform Plus handle for fast and smooth work: Hard handle zones for high working speeds, while soft handle zones guarantee a high torque transfer. Individually tested at 10,000 V for safe working at the approved voltage of 1,000 V. Reduced blade diameter, so that even sunken screws can be easily reached. Take it easy tool finder with colour coding by profile and size stamping - for quick and easy identification of the required tool. The hexagon anti-roll protection avoids screwdrivers from rolling away annoyingly at the workplace.



VDE
TOOL



TAKE IT EASY
TOOL FINDER



EXTRA
SLIM



KRAFTFORM
ERGONOMICS



ANTI
ROLL-OFF

Web link

https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_165_is.html

Wera - 165 iS
05006460001 - 4013288160188

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de


165 iS PZ VDE Insulated screwdriver with reduced blade diameter for Pozidriv screws, PZ 1 x 80 mm
Kraftform Plus – Series 100 VDE



VDE-insulated screwdriver with reduced blade diameter



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Impact strength test



Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces - resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

Prevents hand injuries




The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

Take it easy Tool Finder



Screwdrivers with Take it easy tool finder: colour coding according to profile and size stamp.

Web link
https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_165_is.html

Wera - 165 iS
 05006460001 - 4013288160188

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de

165 iS PZ VDE Insulated screwdriver with reduced blade diameter for Pozidriv screws, PZ 1 x 80 mm
Kraftform Plus – Series 100 VDE



Further versions in this product family:



mm



mm



inch

05006460001	PZ 1	80	98	3 1/8"
05006461001	PZ 2	100	105	4"

Web link

https://products.wera.de/en/screwdrivers_kraftform_plus_series_100_vde_165_is.html

Wera - 165 iS

05006460001 - 4013288160188

Wera Werkzeuge GmbH

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de