

# 950 PKL L-key, metric, chrome-plated, 12 x 248 mm

## L-Keys for Hexagon Socket Screws



<b>EAN:</b>	4013288038708	<b>Size:</b>	248x45x14 mm
<b>Part number:</b>	05022067001	<b>Weight:</b>	273 g
<b>Article number:</b>	950 PKL	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82041100

- L-keys for hexagonal socket screws
- Hex-Plus allows socket head screws to live longer
- Hexagonal ballpoint on the long arm
- High corrosion protection thanks to chrome-plating
- Metric

High quality L-keys for hexagonal socket screws. Hex-Plus offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The ball-end on the long arm allows for reliable working even in difficult installation situations. The precise chrome-plated design ensures high corrosion protection. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.

### Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl.html)

Wera - 950 PKL  
05022067001 - 4013288038708

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

### L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

### Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

### Surface protection



Chrome-plated hexagon L-keys for outstanding surface protection and long service life. High corrosion protection.

### Web link






[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl.html)

Wera - 950 PKL  
05022067001 - 4013288038708

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

L-Keys for Hexagon Socket Screws

Further versions in this product family:

	 mm	 mm	 mm	 inch	 inch
05022050001 <sup>1)</sup>	1.5	90	14	3 1/2"	9/16"
05022052001	2.0	100	16	4"	5/8"
05022054001	2.5	112	18	4 7/16"	23/32"
05022056001	3.0	126	20	5"	25/32"
05022058001	4.0	140	25	5 1/2"	1"
05022060001	5.0	160	28	6 5/16"	1 3/32"
05022062001	6.0	180	32	7 1/16"	1 1/4"
05022063001	7.0	190	34	7 1/2"	1 5/16"
05022064001	8.0	200	36	8"	1 7/16"
05022066001	10.0	219	40	8 11/16"	1 9/16"
<b>05022067001</b>	<b>12.0</b>	<b>248</b>	<b>45</b>	<b>10"</b>	<b>1 3/4"</b>

1) Regular hexagon

Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl.html)

Wera - 950 PKL  
05022067001 - 4013288038708

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de