

## 950 PKL BM L-key, metric, BlackLaser, 1.5 x 90 mm

### L-Keys for Hexagon Socket Screws



<b>EAN:</b>	4013288094988	<b>Size:</b>	90x14x2 mm
<b>Part number:</b>	05027101001	<b>Weight:</b>	2 g
<b>Article number:</b>	950 PKL BM	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82041100

- L-keys for hexagonal socket screws
- Hexagonal ballpoint on the long arm
- BlackLaser for high corrosion protection and long service life
- Metric

High quality L-keys for hexagonal socket screws. The ball-end on the long arm allows for reliable working even in difficult installation situations. The BlackLaser surface treatment provides outstanding surface protection, even against corrosion, and a long service life. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.

#### Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl_bm.html)

Wera - 950 PKL BM  
05027101001 - 4013288094988

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## L-Keys for Hexagon Socket Screws

### L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

### Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

### Surface protection



L-keys with BlackLaser surface treatment for outstanding surface protection and long service life. High corrosion protection.

### Web link






[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl_bm.html)

Wera - 950 PKL BM  
05027101001 - 4013288094988

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

L-Keys for Hexagon Socket Screws

Further versions in this product family:

	 mm	 mm	 mm	 inch	 inch
<b>05027101001<sup>1)</sup></b>	<b>1.5</b>	<b>90</b>	<b>14</b>	<b>3 1/2"</b>	<b>9/16"</b>
05027102001	2.0	100	16	4"	5/8"
05027103001	2.5	112	18	4 7/16"	23/32"
05027104001	3.0	126	19	5"	3/4"
05027105001	4.0	140	25	5 1/2"	1"
05027106001	5.0	160	28	6 5/16"	1 3/32"
05027107001	6.0	180	32	7 1/16"	1 1/4"
05027110001	7.0	190	34	7 1/2"	1 5/16"
05027108001	8.0	200	36	8"	1 7/16"
05027109001	10.0	219	40	8 11/16"	1 9/16"
05027111001	12.0	248	45	10"	1 3/4"

1) Regular hexagon

Web link

[https://products.wera.de/en/l-keys\\_l-keys\\_for\\_hexagon\\_socket\\_screws\\_950\\_pkl\\_bm.html](https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkl_bm.html)

Wera - 950 PKL BM  
05027101001 - 4013288094988

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de