



EAN:	4013288100689	Size:	185x115x35 mm
Part number:	05057122001	Weight:	504 g
Article number:	Bit-Safe 61 Universal 1	Country of origin:	CZ
		Customs tariff number:	82079030

- The Bit-Safes in textile box convince due to their functionality in a minimum of space
- Universal holder with strong permanent magnet and quick-release chuck
- Torsion design against premature wear
- 61-piece


Comprehensive 61-piece bit set by Wera in a robust Bit-Safe. Provides a quick overview of the tools available and bits not needed are simply reinserted into the set and do not get lost. 1 universal holder with Rapidaptor technology: allows bits to be attached without any need to actuate the sleeve. The removal of the bit is simple, just by pushing the sleeve forward - for rapid bit change with just one hand. The strong permanent magnet holds the bits absolutely securely. Can be inserted in the power screwdriver or for use in the chuck of the electric drill.

Web link
<https://www.wera.de/en/05057122001>

Wera - Bit-Safe 61 Universal 1
 05057122001 - 4013288100689

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de

Bit-Safe



The new Bit-Safes provide users with comprehensive bit and holder ranges in a surface-protecting, compact textile box.

TZ-Bits



TZ-Bits are tough viscous bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.

Tough bits



Tough Wera bits prevent the tip from breaking prematurely. Z-bits usually are the bit for universal screwdriving applications.

Rapidaptor holder



Lightning-fast bit change without any extra tools. One-handed operation. With fast-rotating sleeve for easy wielding of the screwdriver.

Chuck-all




The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Rapid-in and self-lock




The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Single-hand function



Every function of the Rapidaptor quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Web link


<https://www.wera.de/en/05057122001>

Wera - Bit-Safe 61 Universal 1
05057122001 - 4013288100689

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de


Set contents:

889/4/1 K Rapidaptor Universal Bit Holder, 1/4" x 50 mm

 05052502001 1x 1/4" x 50 mm




851/1 TZ bits, PH 1 x 25 mm

 05056505001 3x PH 1 x 25 mm
 05056510001 10x PH 2 x 25 mm
 05056525001 2x PH 3 x 25 mm




855/1 TZ bits, PZ 1 x 25 mm

 05056810001 3x PZ 1 x 25 mm
 05056815001 10x PZ 2 x 25 mm
 05056825001 2x PZ 3 x 25 mm




867/1 TZ TORX® bits, TX 10 x 25 mm

 05066305001 2x TX 10 x 25 mm
 05066308001 3x TX 15 x 25 mm
 05066310001 3x TX 20 x 25 mm
 05066312001 3x TX 25 x 25 mm
 05066315001 3x TX 30 x 25 mm
 05066320001 2x TX 40 x 25 mm




800/1 TZ bits, 0.6 x 4.5 x 25 mm

 05056210001 1x 0.6 x 4.5 x 25 mm
 05056225001 1x 1 x 5.5 x 25 mm
 05056233001 1x 1.2 x 6.5 x 25 mm



840/1 Z bits, 2.5 x 25 mm

 05056310001 3x 2.5 x 25 mm
 05056315001 3x 3 x 25 mm
 05056320001 3x 4 x 25 mm
 05056325001 2x 5 x 25 mm



Hook and Loop Fastener Strip 120, 120 x 50 mm

1x 120 x 50 mm



Web link

<https://www.wera.de/en/05057122001>

Wera - Bit-Safe 61 Universal 1
 05057122001 - 4013288100689

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de