Series 7400 Kraftform torque screwdrivers with a customised factory pre-set measurement value, pistol handle, 7463 x 4.0-8.8 Nm Series 7400 Kraftform Torque Screwdrivers, adjustable to customer requirements within the specified measurement range















EAN: 4013288188199 **Size:** 150x100x37 mm

Part number:05074728010Weight:270 gArticle number:7400 customized pre-set,Country of origin:CZ

pistol handle **Customs tariff**

oustonis tann numbor: 82054000

number:

- Customized pre-set torque screwdriver with pistol handle
- Suitable for bits with 1/4" hex head drive
- Rapidaptor technology for rapid bit change
- Distinct signal when pre-set value is reached
- Multi-component Kraftform handle for high working speeds

Wera torque screwdriver. Kraftform pistol handle for particularly high torque transmission, multi-component for high working speeds and particularly ergonomic screwdriving. With a customised factory pre-set torque value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed with an extra tool within the measuring range (re-calibration kit can be ordered with the code number 05137002001). Afterwards you can check the set value using an off-the-shelf torque tester. Rapidaptor quick-release technology for rapid bit changes. Unlimited loosening torque for slackening stuck screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Please note: 1 Ncm = 0.01 Nm.

Series 7400 Kraftform torque screwdrivers with a customised factory pre-set measurement value, pistol handle, 7463 x 4.0-8.8 Nm Series 7400 Kraftform Torque Screwdrivers, adjustable to customer requirements within the specified measurement range



Customised pre-setting



Wera torque screwdriver. With a customised factory pre-set torque value. For all applications, where the same constant torque and repeat accuracy are required.

Versatile



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

Chuck-all



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Rapid-in and self-lock

Pre-set,

screwdrivers



adjustable

torque

The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Unlimited torque



Unlimited torque for loosening seized screws.

Further versions in this product family:

			 				
	art. no.	inch	Nm	mm	mm	inch	inch
050747170101)	7462	1/4"	3.0-6.0	150	100	6"	4"
05074728010 ¹⁾	7463	1/4"	4.0-8.8	150	100	6"	4"

¹⁾ The desired settings can be made in the following units: Nm, kgf. m, lbf. ft., ozf. in., dN. m, kgf. cm, lbf. in, in. oz, cN. m, gf. m, ft. lb, gf. cm, in. lb.

https://products.wera.de/en/torque_tools_series_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_requirements_within_the_specified_measurement_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_to_customer_range_7400_kraftform_torque_screwdrivers_adjustable_torque_screwdrivers_a