Series 7400 ESD Kraftform torque screwdrivers with a customised factory pre-set measurement value, with quick-release chuck, 7455 ESD x 0.1-0.34 Nm 7400 ESD series Kraftform Torque screwdrivers, with factory pre-set value of your choice





- Customized pre-set, adjustable Kraftform ESD torque screwdriver
- ESD-safe tool thanks to surface resistance of  $\leq$  10<sup>9</sup> 0hm
- Kraftform handle for fast and ergonomic screwdriving
- Suitable for bits with 4 mm halfmoon and 4 mm HIOS drive
- Distinct audible and perceivable excess load signal when the pre-set torque value is reached

Wera torque screwdriver. Safe protection against electrostatic charge and associated damage. With a customised factory pre-set torque value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed within the measuring range with the extra tool 05137003001. Afterwards you can check the set value using an off-the-shelf torque tester. Rapidaptor quick-release technology for rapid bit changes. Unlimited loosening torque for slackening stuck screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Suitable for bits with a 4 mm Halfmoon drive (Wera series 9) and a 4 mm HIOS drive (Wera series 21). Please note: 1 Ncm = 0.01 Nm.













Web link

https://products.wera.de/en/torque\_tools\_7400\_esd\_series\_kraftform\_torque\_screwdrivers\_with\_factory\_pre-set\_value\_of\_your\_choice\_7400\_esd\_customized\_pre-set\_halfmontheta\_balance.pre-set\_value\_of\_your\_choice\_7400\_esd\_customized\_pre-set\_halfmontheta\_balance.pre-set\_halfmontheta\_

Series 7400 ESD Kraftform torque screwdrivers with a customised factory pre-set measurement value, with quick-release chuck, 7455 ESD x 0.1-0.34 Nm 7400 ESD series Kraftform Torque screwdrivers, with factory pre-set value of your choice



**Customised pre-setting** 

Wera ESD Tools

High protection

## For Halfmoon and HIOS Bits



Wera torque screwdriver. With a customised factory pre-set torque value. For all applications, where the same constant torque and repeat accuracy are required.



The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.



The electric surface resistance of the Wera ESD material is  $\leq$  10<sup>9</sup> ohm. This securely protects components against electrostatic energy and associated damage.



Features a combination bit holder for both bits with Halfmoon and bits with HIOS drive.

## Kraftform



The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

Web link https://products.wera.de/en/torque\_tools\_7400\_esd\_series\_kraftform\_torque\_screwdrivers\_with\_factory\_pre-set\_value\_of\_your\_choice\_7400\_esd\_customized\_pre-set\_halfmodest and the series and the s

Series 7400 ESD Kraftform torque screwdrivers with a customised factory pre-set measurement value, with quick-release chuck, 7455 ESD x 0.1-0.34 Nm 7400 ESD series Kraftform Torque screwdrivers, with factory pre-set value of your choice



Further versions in this product family:

		<b> </b> +++ <b> </b> ++++ <b> </b>		[] ▲ [] <sub>¥</sub>	∏ ▲ U v
	art. no.	Nm	mm	mm	inch
05074826010 <sup>1)</sup>	7455 ESD	0.1-0.34	89	138	5 1/4"
050748280101)	7456 ESD	0.3-1.0	89	138	5 1/4"

1) The desired settings can be made in the following units: Nm, kgf. m, lbf. ft., ozf. in., dN. m, kgf. cm, lbf. in, in. oz, cN. m, gf. m, ft. lb, gf. cm, in. lb.

Web link https://products.wera.de/en/torque\_tools\_7400\_esd\_series\_kraftform\_torque\_screwdrivers\_with\_factory\_pre-set\_value\_of\_your\_choice\_7400\_esd\_customized\_pre-set\_halfmodest and the series and the s