

Click-Torque Lock C 3 R/L Torque wrench, adjustable, Torque function, square head insert (1/2"), clockwise/counterclockwise torque operation, 40-200 Nm, 1/2" x 40-200 Nm

Click-Torque Lock R/L series - adjustable torque wrenches with Torque Lock function



EAN:	4013288233660	Size:	540x60x60 mm
Part number:	05075695001	Weight:	1600 g
Article number:	Click-Torque Lock C 3 R/L	Country of origin:	TW
		Customs tariff number:	82041100

- For clockwise and counterclockwise operation
- Torque Lock function: The torque function can be deactivated so that the tool can also be used for loosening
- With square head insert (including patent-registered socket locking)
- Extra click: audible and tactile torque setting
- Torque wrench gives an audible and tactile signal
- Measuring range: 40-200 Nm; precision $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07

Adjustable torque wrench for controlled clockwise and counterclockwise torque operation. With 1/2" square head drive. The torque function can be deactivated (Torque Lock function), so that the tool can also be used for loosening. Easy setting and saving of the default value. The audible and tactile clicks on reaching the scale values facilitate the safe setting of the desired torque value. The robust release mechanism guarantees a clearly audible and tactile release signal when the set torque value is reached. Fine-toothed reversible ratchet with 45 teeth. Accuracy of $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07.



Web link

https://products.wera.de/en/torque_tools_series_click-torque_wrenches_click-torque_lock_r_l_series_-_adjustable_torque_wrenches_with_torque_lock_function_click-torque_

Wera - Click-Torque Lock C 3 R/L
05075695001 - 4013288233660

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Click-Torque Lock C 3 R/L Torque wrench, adjustable, Torque function, square head insert (1/2"), clockwise/counterclockwise torque operation, 40-200 Nm, 1/2" x 40-200 Nm

Click-Torque Lock R/L series - adjustable torque wrenches with Torque Lock function



Torque Lock function

With external square head tip

Exact

Easy and safe




The torque function can be deactivated so that the tool can also be used for loosening.



With square head insert (including patent-registered socket locking) for controlled clockwise and counterclockwise torque operation.



Precision of $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07.



Easy setting and saving of the desired torque value; easy to read on main and fine scales.

For right and left direction

Setting with Speed


Release mechanism



The Click-Torque torque wrench is suitable for clockwise and counterclockwise torque operation. Very smooth change of direction thanks to captive square head insert.




With audible and tactile locking when the scale values are reached.



On reaching the desired torque value, an audible and tactile mechanism is triggered.

Further versions in this product family:



	inch	inch	mm	mm	inch	inch	mm	mm	inch	lbf. ft.	Nm	inch	mm	Nm
05075695001 ¹⁾	5 1/2"	23/32"	140	18.4	1	1	47	43	20	30-14	40-20	1/2"	512	1.0
					27/32"	11/16"			5/32"	6	0			

1) Available from September 2025

Web link

https://products.wera.de/en/torque_tools_series_click-torque_wrenches_click-torque_lock_r_l_series_-_adjustable_torque_wrenches_with_torque_lock_function_click-torque_l

Wera - Click-Torque Lock C 3 R/L
05075695001 - 4013288233660

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de