



EAN:	4013288236586	Size:	550x120x120 mm
Part number:	05075790001	Weight:	3310 g
Article number:	Click-Torque Lock C 3 Set 1	Country of origin:	TW
		Customs tariff number:	82041100

- Tool set for the car wheel change
- Car wheel change set with Click-Torque Lock: controlled tightening and loosening with only one tool
- Assembly and disassembly with one torque wrench
- One Click-Torque Lock C 3 torque wrench, 1/2", adjustable, reversible ratchet, Torque Lock function
- Torque Lock function: The torque function can be deactivated so that the tool can also be used for loosening screws and bolts
- Extra click: audible and tactile torque setting
- Torque wrench gives an audible and tactile signal
- Measuring range: 40-200 Nm; precision $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07

5-piece set for the car wheel change. One Click-Torque Lock C 3 (40-200 Nm) torque wrench with Torque Lock function. The torque function can be deactivated so that the tool can also be used for loosening screws and bolts. Precision $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07. 3 sockets (1/2"; sizes 17.0; 19.0; 21.0) with fast-rotating plastic sleeve for higher working speeds, better welding during screwdriving and extra protection of the rim. One extension (125 mm long); with cross hole and ring socket to attach the safety pin and safety ring of machine operated tools. In a robust textile box with twist-to-unlock mechanism, which ensures that the sockets are stored securely and can be easily removed using the rotating mechanism.



Web link
<https://www.wera.de/en/05075790001>

Wera - Click-Torque Lock C 3 Set 1
 05075790001 - 4013288236586

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de

Click-Torque Lock car wheel change set



The professional solution for the car wheel change. Precise and secure tightening of wheel nuts using the Click-Torque Lock C 3 torque wrench. The Torque Lock function also allows screws and bolts to be loosened without torque. Three robust sockets with rotating plastic sleeve and protection for wheel screws offer the transmission of high forces without loading the edges of the bolt. Low-lying wheel screws can also be reached with the extension (125 mm long).

Click-Torque Lock torque wrench



Click-Torque Lock torque wrenches stand out with their robust design. Easy to set and save the desired torque value. Precision of $\pm 3\%$ as per DIN EN ISO 6789-1:2017-07. Click-Torque Lock torque wrenches are essential tools for torque-controlled, safe and reliable screw connections.

Torque Lock function



The torque function can be deactivated so that the tool can also be used for loosening screws and bolts.

With external square head tip



With 1/2" external square head tip (including patent-registered socket locking).

Impact wrench proof



The Wheel Impaktor sockets are designed for use with electric or pneumatic impact wrenches due to their robust Impaktor technology.

Smooth plastic sleeve



The rotating plastic sleeve allows for higher control during screwdriving. In addition, the surface of the rim is protected. The plastic sleeves are interchangeable.

Protection for wheel bolts



The internal plastic insert protects the surfaces of the wheel bolts.

Web link

<https://www.wera.de/en/05075790001>

Wera - Click-Torque Lock C 3 Set 1
05075790001 - 4013288236586

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Set contents:

Click-Torque Lock C 3 Torque wrench, adjustable, reversible ratchet, Torque Lock function, 40-200 Nm, 1/2" x 40-200 Nm

05075692001 1x 1/2" x 40-200 Nm



8790 C Wheel Impaktor Socket with 1/2" drive, 17 x 85 x 30 mm



05004590001 1x 17 x 85 x 30 mm

05004591001 1x 19 x 85 x 30 mm

05004592001 1x 21 x 85 x 32 mm



8894 SC extension, short, 1/2", 1/2" x 125 mm



1x 1/2" x 125 mm



7762 Click-Torque collar M3, 55 x 21.5 mm

05078709001 1x 55 x 21.5 mm



Web link

<https://www.wera.de/en/05075790001>

Wera - Click-Torque Lock C 3 Set 1
05075790001 - 4013288236586

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de