Safe-Torque A 1 Imperial Set 1, 1/4" square head drive, 2-12 Nm, 10 pieces

EAN:	4013288223074	**Size:**	275x140x65 mm
Part number:	05075831001	**Weight:**	1023 g
Article number:	Safe-Torque A 1 Imperial Set 1	**Country of origin:**	CZ
		Customs tariff number:	82041100

- Slip-over release mechanism - the set torque can never be overtightened
- Torque Lock function: The torque function can be deactivated and the tool can then be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation
- For controlled clockwise and counterclockwise torque operation - tightening and loosening with or without torque
- Easy setting and saving of the desired torque value with audible and tactile clicks when reaching the scale values
- After the target torque has been reached, the release angle is only 30°
- Accuracy ±10%
- The fine toothing with 72 teeth allows for a low return angle of 5°
- 1/4" square head drive with socket locking

10-piece 1/4" torque wrench set in a robust textile box; torque wrench with slide-over mechanism. Once the set torque has been reached, the tool cannot be overtightened, so that excessive torque cannot be applied. Setting range of 2 to 12 Nm for controlled clockwise and counterclockwise torque operation. Easy setting and saving of the default value: The audible and tactile clicks on reaching the scale values facilitate the safe setting of the desired torque value. The Torque Lock function allows use as a standard ratchet without torque function. Thus also usable for applications with angles of rotation. Accuracy ±10%. Max. breaking torque of the ¼" square head as per DIN 3122. The return angle of only 5° allows the ratchet to be used even in confined spaces. Included are: Safe-Torque A 1 torque wrench, 1/4" square head, 2-12 Nm, 8 sockets with 1/4" drive and one short extension.

TORQUE TOOL
ADJUSTABLE
FOR BOTH DIRECTIONS
SAFE TORQUE
ON / OFF TORQUE LOCK
PRESS TO UNLOCK
TAKE IT EASY TOOL FINDER
TWIST TO UNLOCK
ULTRA COMPACT
WERA 2GO COMPATIBLE
RAPID SPIN SLEEVE

Web link
https://www.wera.de/en/05075831001

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Safe-Torque

Slide-over mechanism prevents application of excessive torques

The Safe-Torque A 1 torque wrench is equipped with a slide-over mechanism. Once the set torque value has been reached, the tool cannot be overtightened, so that excessive torque cannot be applied.

Torque Lock function

The torque function can be deactivated. The Safe-Torque torque wrench can then also be used as a standard ratchet with high loosening moments and for applications with defined angles of rotation.

For clockwise and counterclockwise operation

The Safe-Torque torque wrench is suitable for clockwise and counterclockwise operation with a set torque. When the Torque Lock function is deactivated, tightening and loosening is enabled without torque.

Easy torque setting

Easy setting and saving of the required torque with audible and tactile clicks on reaching the scale values.

Low return angle

The fine-toothed Safe-Torque torque wrench with 72 teeth has a back-pivoting angle of only 5°. The small stroke offers quick and precise working in all installation positions.

For 1/4" sockets

The Safe-Torque A 1 torque wrench has 1/4" square head mounting and is suitable for 1/4" sockets.

Space for more tools

The Wera Belts can be attached to the hook-and-loop fastener strips in the textile box of the sets Safe-Torque A 1 Set 1 and Safe-Torque A 1 Imperial Set 1, so more sockets and/or bit sockets can be stored and transported.

Web link
https://www.wera.de/en/05075831001

Wera - Safe-Torque A 1 Imperial Set 1
05075831001 - 4013288223074

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Set contents:

Safe-Torque A 1 torque wrench with 1/4" square head drive, 2-12 Nm, 1/4" x 2-12 Nm

05075800001	1x	1/4" x 2-12 Nm

8790 HMA Zyklop 1/4" socket, 3/16" x 23 mm

05003514001	1x	3/16" x 23 mm
05003515001	1x	7/32" x 23 mm
05003516001	1x	1/4" x 23 mm
05003517001	1x	9/32" x 23 mm
05003518001	1x	5/16" x 23 mm
05003520001	1x	3/8" x 23 mm
05003521001	1x	7/16" x 23 mm
05003522001	1x	1/2" x 23 mm

8794 SA Zyklop extension with free-turning sleeve, short, 1/4", 1/4" x 75 mm

05003525001	1x	1/4" x 75 mm

Hook and Loop Fastener Strip 240, 50 x 240 mm

	1x	50 x 240 mm

Web link
https://www.wera.de/en/05075831001

Wera - Safe-Torque A 1 Imperial Set 1
05075831001 - 4013288223074

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de