# 165 i PZ/S SB VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted), # 1 x 80 mm

Kraftform Plus - Series 100 VDE













**EAN:** 4013288186584 **Size:** 235x50x30 mm

Part number:05100021001Weight: $67 \, \mathrm{g}$ Article number: $165 \, \mathrm{i} \, \mathrm{PZ/S} \, \mathrm{SB}$ Country of origin:CZ

Customs tariff 82054000

number:

• Insulated blades for secure work at 1,000 volts

- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Handle markings simplify finding and sorting of tools
- Hexagonal anti-roll feature against rolling away
- Combination profile Phillips / slotted

Wera VDE screwdrivers with multi-component Kraftform Plus handle for fast and low-fatigue working: hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. Combination profile - slotted and Pozidriv\* particularly for jobs on terminal blocks, fuse boxes, switches and relays. Individually tested in water bath at 10,000 volts for secure work at the permissible voltage of 1,000 volts. The hexagonal anti-roll feature prevents any bothersome rolling away at the workplace.

Web link

 $https://products.wera.de/en/screwdrivers\_kraftform\_plus\_\_series\_100\_vde\_165\_i\_pz\_s\_sb.html$ 

# 165 i PZ/S SB VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted), # 1 x 80 mm

### Kraftform Plus - Series 100 VDE



#### PlusMinus screwdrivers



For the use in terminal blocks, control cabinets, switches, relays, sockets etc.

### Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

### Impact strength test



Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.

### Multicomponent Kraftform handle

loads up to 1,000 volts.

The individual testing at 10,000

volts, in accordance with IEC

60900, ensures safe working with



Wera produces the Kraftform handle out of several materials with different properties. resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces - resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

### Prevents hand injuries




The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

### Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

### Identification marking



The screw profile and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case, or at the workplace.

 $Web\ link \\ https://products.wera.de/en/screwdrivers\_kraftform\_plus\_\_series\_100\_vde\_165\_i\_pz\_s\_sb.html$ 

Wera - 165 i PZ/S SB 05100021001 - 4013288186584

# 165 i PZ/S SB VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted), # 1 x 80 mm

Kraftform Plus - Series 100 VDE



### Set contents:

165 i PZ/S VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted), # 1 x 80 mm 05006190001 1x # 1 x 80 mm



Web link https://products.wera.de/en/screwdrivers\_kraftform\_plus\_\_series\_100\_vde\_165\_i\_pz\_s\_sb.html Wera - 165 i PZ/S SB

05100021001 - 4013288186584