

840/1 Z bits, 5/32" x 25 mm

Bits for Hexagon Socket Screws



<b>EAN:</b>	4013288036506	<b>Size:</b>	25x7x6 mm
<b>Part number:</b>	05135074001	<b>Weight:</b>	5 g
<b>Article number:</b>	840/1 Z Hex-Plus	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For socket head screws
- Hex-Plus allows socket head screws to live longer
- Tough for hard materials
- 1/4" hexagon drive (Wera connecting series 1)

Tough Wera bits for hexagonal socket screws, for universal use. Hex-Plus offers larger contact surfaces in the screw head. The notch effect is reduced to a minimum and the destruction of the screw is nearly eliminated. 1/4" hexagonal, suitable for holding tools as per DIN ISO 1173-D 6.3.

**Web link**

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_and\\_sets\\_the\\_range\\_of\\_bits\\_bits\\_for\\_hexagon\\_socket\\_screws\\_840\\_1\\_z\\_hex-plus.html](https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_hexagon_socket_screws_840_1_z_hex-plus.html)

Wera - 840/1 Z Hex-Plus  
05135074001 - 4013288036506

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

### Hex-Plus



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.





### Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_and\\_sets\\_the\\_range\\_of\\_bits\\_bits\\_for\\_hexagon\\_socket\\_screws\\_840\\_1\\_z\\_hex-plus.html](https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_hexagon_socket_screws_840_1_z_hex-plus.html)

Wera - 840/1 Z Hex-Plus  
05135074001 - 4013288036506

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

Further versions in this product family:

				
	mm	inch	mm	inch
05056303001	1.5	-	25	1"
05056305001	2.0	-	25	1"
05056310001	2.5	-	25	1"
05056315001	3.0	-	25	1"
05056320001	4.0	-	25	1"
05056325001	5.0	-	25	1"
05056330001	6.0	-	25	1"
05056332001	7.0	-	25	1"
05056335001	8.0	-	25	1"
05056340001	10.0	-	25	1"
05135060001	-	0.05"	25	1"
05135070001	-	1/16"	25	1"
05135071001	-	5/64"	25	1"
05135072001	-	3/32"	25	1"
05135078001	-	7/64"	25	1"
05135073001	-	1/8"	25	1"
05135069001	-	9/64"	25	1"
<b>05135074001</b>	-	<b>5/32"</b>	<b>25</b>	<b>1"</b>
05135075001	-	3/16"	25	1"
05135079001	-	7/32"	25	1"
05135076001	-	1/4"	25	1"
05135077001	-	5/16"	25	1"
05135068001	-	3/8"	25	1"

**Web link**
[https://products.wera.de/en/bits\\_holders\\_adaptors\\_and\\_sets\\_the\\_range\\_of\\_bits\\_bits\\_for\\_hexagon\\_socket\\_screws\\_840\\_1\\_z\\_hex-plus.html](https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_hexagon_socket_screws_840_1_z_hex-plus.html)

 Wera - 840/1 Z Hex-Plus  
 05135074001 - 4013288036506

 Wera Werkzeuge GmbH  
 Korzter Straße 21-25  
 D-42349 Wuppertal  
 Tel: +49 (0)2 02 / 40 45-0  
 E-Mail: info@wera.de